


# Dynamic Envelope Printer



**INTOPRINT TECHNOLOGIES**



## DP100GA


- Prints 55 full-color envelopes per minute
- A top-load bottom-feed feeder and a coordinated high-capacity conveyor insures continuous production
- Capable of feeding a wide variety of products and sizes such as envelopes, card stock, postcards, labels, standard paper, and more.
- Feeds sizes from 3" x 5" up to 12" x 18"
- Prints return address, logo, mailing address, bar code, and personalized messages all in one pass.
- Feeding letterhead stock from the standard paper drawers allows for an exact color-match between letterhead, business cards, and printed envelopes.
- Excellent color matching provided by the embedded Fiery System 8e.

See it on the web at: <http://www.intoprinttech.com>

**Intoprint Technologies**

5119 Hollins Road • Roanoke, VA 24019 • (540) 362-1226 • Toll Free 1-800-833-4493

# Dynamic Envelope Printer



**INTOPRINT TECHNOLOGIES**



## DP100GA TECHNICAL SPECIFICATIONS

### Printer

- **Print Speed:** Up to 36 ppm Color; up to 40 ppm Monochrome (Letter-size); Up to 55 ppm Color/Monochrome (#10 Envelopes)
- **Processor:** EFI®X8e 1 GHz Intel® Celeron®
- **File Storage:** 40 GB Hard Disk Drive
- **Print Resolution:** True 1200 x 1200 dpi (with HD color technology)
- **Print Technology:** CMYK LED Technology
- **Duty Cycle:** Up to 150,000 pages per month
- **Connectivity:** RJ-11, RJ-45; USB v2.0
- **Network I/F:** OkiLAN® 10/100 Base-T Internal Ethernet Print Server Standard
- **Emulations:** PCL® 5c, PCL 6; Adobe® PostScript 3 standard
- **Operating Systems:** Stand-alone and network - Windows Vista® (32/64-bit), XP (32/64-bit), 2003 Server (32/64-bit), 2000; Mac® OS X 10.4.3 and higher
- **Resident Scalable Fonts:** 136 Adobe Postscript fonts; 45 PCL fonts
- **Bitmap (PCL) Fonts:** Line printer, OCR-A and OCR-B

### Networking

- **Auto Protocol and Port Switching**
- **IPv6 Support and SSL Support:** IP over SSL, LDAP over SSL
- **SNMP v3 Support**
- **Auto IP:** DHCP and BOOTP
- **NDS and SMB Support**
- **AppleTalk® and NetWare 6 Compliant:** IPP, NDDS gateway printing, point-and-print
- **Port 9100 (with BiDi Support)**
- **IPP Support**
- **Bonjour Support (formerly Rendezvous)**

### System Memory

- **Standard/Maximum Imaging RAM:** 1 GB
- **Image Processing RAM:** 384 MB

### Paper Handling

- **Envelope Sizes:** Min 3" x 5"; Max 10" x 13"
- **Paper Sizes:** Min 3" x 5"; Max 12.9" x 47.25"
- **Printer Paper Input:** 1,060 sheets standard (2 x 530-sheet tray)
- **Feeder Paper Input:** Up to 1,000 sheets
- **Paper Weight:** Trays 1 and 2 - 17 lb. bond-80 lb. cover (64-216 gsm); Multipurpose tray - 17 lb. bond-170 lb. index (64-307 gsm); duplex - 20 lb. bond-65 lb. cover (75-188 gsm) for letter and tabloid sheets
- **Automatic Duplexer:** 2-sided printing standard
- **Paper Output:** Face-down stacker 500 sheets; Conveyor 1000 envelopes

### Environmental

- **HxWxD without Feeder:** 54.88" x 26.48" x 34.59"
- **HxWxD with Feeder:** 108" x 26.48" x 34.59"
- **Power Consumption:** Typical 750W, Peak 1500W, Idle 200W (average), Power Save Mode: <80W
- **ENERGY STAR® Compliance:** Yes

### Color Controls

- **Ink Simulations:** SWOP®, Euroscale and others
- **Color Matching Modes:** sRGB, Monitor simulations
- **Spot Color Matching:** PANTONE® Color Matching System (Spot-On Fiery Add-on) - Standard
- **Color Management:** EFI ColorWise Pro Tools; provides calibration, and the ability to manage input/output profiles
- **EFI Fiery Technology:** ColorWise Pro Tools; Freeform (Variable Data)

### Consumables

- Refer to proposal for details

### Options

- 3 drawer, 1,590 Sheet High Capacity Feeder (provides 2,160 total)



**Intoprint Technologies**

5119 Hollins Road • Roanoke, VA 24019 • (540) 362-1226 • Toll Free 1-800-833-4493